



0.5 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /±15 VDC Current (mA) Nom/Max	Size
CA018-2001	0.5	18.0	18	±2.5	5.0	5	15	2.0:1/1.5:1	2.0:1/1.5:1	120	<u>K2</u>
CA018-2002	0.5	18.0	18	±2.5	5.0	8	18	2.0:1/1.5:1	2.0:1/1.5:1	130	<u>K2</u>
CA018-2003	0.5	18.0	18	±2.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	140	<u>K2</u>
CA018-2004	0.5	18.0	18	±2.5	5.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	150	<u>K2</u>
CA018-2005	0.5	18.0	17	±2.5	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	160	<u>K2</u>
CA018-2006	0.5	18.0	16	±2.5	5.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	200	<u>K2</u>
CA018-2020	0.5	18.0	14	±2.5	6.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	<u>K2</u>
CA018-2022	0.5	18.0	14	±2.5	6.0	22	32	2.0:1/1.5:1	2.0:1/1.5:1	350	<u>K2</u>
CA018-2024	0.5	18.0	12	±2.5	6.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	400	<u>K2</u>
CA018-2026	0.5	18.0	18	±2.0	6.0	26	36	2.0:1/1.5:1	2.0:1/1.5:1	650	<u>K2</u>
CA018-2027	0.5	18.0	15/18	±2.0/±1.5	7.5/6.0	27/29	37	2.0:1/1.7:1	2.3:1/1.8:1	785	<u>K3S</u>
CA018-2028	0.5	18.0	16/19	±2.0/±1.5	7.5/6.0	28/30	38	2.0:1/1.7:1	2.3:1/1.8:1	800	<u>K3S</u>
CA018-2030	0.5	18.0	17/20	±2.0/±1.5	7.5/6.0	30/32	40	2.0:1/1.7:1	2.3:1/1.8:1	820	<u>K3S</u>
CA018-3001	0.5	18.0	26	±2.5	5.0	5	15	2.0:1/1.5:1	2.0:1/1.5:1	180	<u>K3S</u>
CA018-3002	0.5	18.0	26	±2.5	5.0	8	18	2.0:1/1.5:1	2.0:1/1.5:1	190	<u>K3S</u>
CA018-3003	0.5	18.0	26	±2.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3004	0.5	18.0	26	±2.5	5.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	210	<u>K3S</u>
CA018-3005	0.5	18.0	26	±2.5	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	220	<u>K3S</u>
CA018-3006	0.5	18.0	26	±2.5	5.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	260	<u>K3S</u>
CA018-3020	0.5	18.0	26	±2.5	5.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	345	<u>K3S</u>
CA018-3022	0.5	18.0	25/29	±1.5/±1.0	4.0/3.5	22/24	32	2.2:1/1.5:1	2.2:1/1.5:1	420	<u>K3S</u>
CA018-3024	0.5	18.0	26	±2.5	6.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	750	<u>K3S</u>
CA018-3026	0.5	18.0	26	±2.5	6.0	26	36	2.0:1/1.5:1	2.0:1/1.5:1	800	<u>K3S</u>
CA018-3027	0.5	18.0	20/25	±2.0/±1.5	7.5/5.0	27	37	2.25:1/1.5:1	2.25:1/1.5:1	850*	<u>K3S</u>
CA018-3029	0.5	18.0	20/25	±2.0/±1.5	7.5/5.0	29/31	39	2.25:1/1.5:1	2.25:1/1.5:1	950*	<u>K3S-NR</u>
CA018-3029-1	0.5	18.0	20/25	±2.0/±1.5	7.5/5.0	29/31	39	2.25:1/1.5:1	2.25:1/1.5:1	950*	<u>K3S-NR</u>
CA018-3030	0.5	18.0	25/28	±2.0/±1.5	6.0/4.0	30/32	40	2.0:1/1.7:1	2.3:1/1.8:1	900	<u>K3S</u>
CA018-3009	0.5	18.0	26	±2.5	4.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3010	0.5	18.0	26	±2.5	3.8	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	<u>K3S</u>

Note 1: Min/Max

Ciao Wireless, Inc.
 4000 Via Pescador / Camarillo / CA 93012
 Tel (805) 389-3224 / Fax (805) 389-3629 / ciaowireless.com



0.5 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /±15 VDC Current (mA) Nom/Max	Size
CA018-4001	0.5	18.0	34	±2.5	5.0	5	15	2.0:1/1.5:1	2.0:1/1.5:1	240	<u>K4</u>
CA018-4002	0.5	18.0	34	±2.5	5.0	8	18	2.0:1/1.5:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4003	0.5	18.0	34	±2.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	260	<u>K4</u>
CA018-4004	0.5	18.0	34	±2.5	6.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	270	<u>K4</u>
CA018-4005	0.5	18.0	34	±2.5	6.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	280	<u>K4</u>
CA018-4006	0.5	18.0	34	±2.5	6.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	320	<u>K4</u>
CA018-4020	0.5	18.0	34	±2.5	6.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	405	<u>K4</u>
CA018-4022	0.5	18.0	34	±2.5	6.0	22	32	2.0:1/1.5:1	2.0:1/1.5:1	550	<u>K4</u>
CA018-4024	0.5	18.0	34	±2.5	6.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	750	<u>K4</u>
CA018-4026	0.5	18.0	34	±2.5	6.0	26	36	2.0:1/1.5:1	2.0:1/1.5:1	850	<u>K4</u>
CA018-4027	0.5	18.0	31/33	±2.0/±1.5	6.0/3.5	27/29	37	2.0:1/1.7:1	2.3:1/1.8:1	905	<u>K4</u>
CA018-4028	0.5	18.0	32/34	±2.0/±1.5	6.0/3.5	28/30	38	2.0:1/1.7:1	2.3:1/1.8:1	930	<u>K4</u>
CA018-4030	0.5	18.0	33/36	±2.0/±1.5	6.0/3.5	30/32	40	2.0:1/1.7:1	2.3:1/1.8:1	950	<u>K4</u>
CA018-4120	0.5	18.0	28/34	±2.5	6.0	20	32	2.0:1/1.5:1	2.0:1/1.5:1	550	<u>K4</u>
CA018-4120-1	0.5	18.0	¹ 28/35	±2.5	6.5/5.0	20	32	2.0:1/1.5:1	2.0:1/1.5:1	550	<u>K3S</u>
CA018-4120L-1	0.5	18.0	¹ 28/35	±2.5	8.0/5.0	20	32	2.0:1/1.5:1	2.0:1/1.5:1	550	<u>K3S</u>
CA018-4009	0.5	18.0	34	±2.5	4.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	260	<u>K4</u>
CA018-4010	0.5	18.0	34	±2.5	3.8	10	20	2.0:1/1.5:1	2.0:1/1.5:1	260	<u>K4</u>
CA018-305015	0.5	18.0	30/35	±2.0/±1.5	5.0/4.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	260	<u>K4</u>
CA018-305017	0.5	18.0	30/35	±2.0/±1.5	5.0/4.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	285	<u>K4</u>

Note 1: Min/Max

Ciao Wireless, Inc.
 4000 Via Pescador / Camarillo / CA 93012
 Tel (805) 389-3224 / Fax (805) 389-3629 / ciaowireless.com



0.5 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /-15 VDC Current (mA) Nom/Max	Size
CA018-3012	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	0	10	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K4</u>
CA018-3013	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	3	13	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K4</u>
CA018-3014	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	5	15	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K4</u>
CA018-3015	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	8	18	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3016	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	10	20	2.3:1/1.6:1	2.0:1/1.5:1	220	<u>K3S</u>
CA018-3017	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	13	23	2.3:1/1.6:1	2.0:1/1.5:1	240	<u>K3S</u>
CA018-3018	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	15	25	2.3:1/1.6:1	2.0:1/1.5:1	260	<u>K3S</u>
CA018-3019	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	18	28	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K3S</u>
CA018-3120	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	20	30	2.3:1/1.6:1	2.0:1/1.5:1	320	<u>K3S</u>
CA018-3123	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	23	33	2.3:1/1.6:1	2.0:1/1.5:1	350	<u>K3S</u>
CA018-3124	0.5	18.0	30/35	±2.0/±1.5	3.5/2.9	24	34	2.3:1/1.6:1	2.0:1/1.5:1	400	<u>K3S</u>
CA018-3042	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	0	10	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3043	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	3	13	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3044	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	5	15	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3045	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	8	18	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3046	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	10	20	2.3:1/1.6:1	2.0:1/1.5:1	220	<u>K3S</u>
CA018-3047	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	13	23	2.3:1/1.6:1	2.0:1/1.5:1	240	<u>K3S</u>
CA018-3048	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	15	25	2.3:1/1.6:1	2.0:1/1.5:1	260	<u>K3S</u>
CA018-3049	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	18	28	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K3S</u>
CA018-3220	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	20	30	2.3:1/1.6:1	2.0:1/1.5:1	320	<u>K3S</u>
CA018-3223	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	23	33	2.3:1/1.6:1	2.0:1/1.5:1	350	<u>K3S</u>
CA018-3224	0.5	18.0	30/35	±2.0/±1.5	3.2/2.7	24	34	2.3:1/1.6:1	2.0:1/1.5:1	400	<u>K3S</u>
CA018-3000	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	0	10	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3031	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	3	13	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3032	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	5	15	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3033	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	8	18	2.3:1/1.6:1	2.0:1/1.5:1	200	<u>K3S</u>
CA018-3034	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	10	20	2.3:1/1.6:1	2.0:1/1.5:1	220	<u>K3S</u>
CA018-3035	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	13	23	2.3:1/1.6:1	2.0:1/1.5:1	240	<u>K3S</u>
CA018-3036	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	15	25	2.3:1/1.6:1	2.0:1/1.5:1	260	<u>K3S</u>
CA018-3037	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	18	28	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K3S</u>
CA018-3320	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	20	30	2.3:1/1.6:1	2.0:1/1.5:1	320	<u>K3S</u>
CA018-3323	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	23	33	2.3:1/1.6:1	2.0:1/1.5:1	350	<u>K3S</u>
CA018-3324	0.5	18.0	30/35	±2.0/±1.5	3.0/2.5	24	34	2.3:1/1.6:1	2.0:1/1.5:1	400	<u>K3S</u>

Ciao Wireless, Inc.

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / ciaowireless.com



0.5 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /-15 VDC Current (mA) Nom/Max	Size
CA018-4012	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	0	10	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4013	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	3	13	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4014	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	5	15	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4015	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	8	18	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4016	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	10	20	2.3:1/1.6:1	2.0:1/1.5:1	270	<u>K4</u>
CA018-4017	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	13	23	2.3:1/1.6:1	2.0:1/1.5:1	290	<u>K4</u>
CA018-4018	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	15	25	2.3:1/1.6:1	2.0:1/1.5:1	280	<u>K4</u>
CA018-4019	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	18	28	2.3:1/1.6:1	2.0:1/1.5:1	350	<u>K4</u>
CA018-4220	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	20	30	2.3:1/1.6:1	2.0:1/1.5:1	370	<u>K4</u>
CA018-4223	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	23	33	2.3:1/1.6:1	2.0:1/1.5:1	400	<u>K4</u>
CA018-4224	0.5	18.0	40/45	±2.0/±1.5	3.5/2.9	24	34	2.3:1/1.6:1	2.0:1/1.5:1	450	<u>K4</u>
CA018-4032	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	0	10	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4033	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	3	13	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4034	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	5	15	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4035	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	8	18	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4036	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	10	20	2.3:1/1.6:1	2.0:1/1.5:1	270	<u>K4</u>
CA018-4037	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	13	23	2.3:1/1.6:1	2.0:1/1.5:1	290	<u>K4</u>
CA018-4038	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	15	25	2.3:1/1.6:1	2.0:1/1.5:1	280	<u>K4</u>
CA018-4039	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	18	28	2.3:1/1.6:1	2.0:1/1.5:1	350	<u>K4</u>
CA018-4320	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	20	30	2.3:1/1.6:1	2.0:1/1.5:1	370	<u>K4</u>
CA018-4323	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	23	33	2.3:1/1.6:1	2.0:1/1.5:1	400	<u>K4</u>
CA018-4324	0.5	18.0	40/45	±2.0/±1.5	3.2/2.7	24	34	2.3:1/1.6:1	2.0:1/1.5:1	450	<u>K4</u>
CA018-4042	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	0	10	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4043	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	3	13	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4044	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	5	15	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4045	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	8	18	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K4</u>
CA018-4046	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	10	20	2.3:1/1.6:1	2.0:1/1.5:1	270	<u>K4</u>
CA018-4047	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	13	23	2.3:1/1.6:1	2.0:1/1.5:1	290	<u>K4</u>
CA018-4048	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	15	25	2.3:1/1.6:1	2.0:1/1.5:1	280	<u>K4</u>
CA018-4049	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	18	28	2.3:1/1.6:1	2.0:1/1.5:1	350	<u>K4</u>
CA018-4420	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	20	30	2.3:1/1.6:1	2.0:1/1.5:1	370	<u>K4</u>
CA018-4423	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	23	33	2.3:1/1.6:1	2.0:1/1.5:1	400	<u>K4</u>
CA018-4424	0.5	18.0	40/45	±2.0/±1.5	3.0/2.5	24	34	2.3:1/1.6:1	2.0:1/1.5:1	450	<u>K4</u>

Ciao Wireless, Inc.

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / ciaowireless.com



0.5 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /-15 VDC Current (mA) Nom/Max	Size
CA018-5012	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	0	10	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K6</u>
CA018-5013	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	3	13	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K6</u>
CA018-5014	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	5	15	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K6</u>
CA018-5015	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	8	18	2.3:1/1.6:1	2.0:1/1.5:1	250	<u>K6</u>
CA018-5016	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	10	20	2.3:1/1.6:1	2.0:1/1.5:1	270	<u>K6</u>
CA018-5017	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	13	23	2.3:1/1.6:1	2.0:1/1.5:1	290	<u>K6</u>
CA018-5018	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	15	25	2.3:1/1.6:1	2.0:1/1.5:1	280	<u>K6</u>
CA018-5019	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	18	28	2.3:1/1.6:1	2.0:1/1.5:1	350	<u>K6</u>
CA018-5120	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	20	30	2.3:1/1.6:1	2.0:1/1.5:1	370	<u>K6</u>
CA018-5123	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	23	33	2.3:1/1.6:1	2.0:1/1.5:1	400	<u>K6</u>
CA018-5124	0.5	18.0	50/55	±2.0/±1.5	3.5/2.9	24	34	2.3:1/1.6:1	2.0:1/1.5:1	450	<u>K6</u>
CA018-5032	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	0	10	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K6</u>
CA018-5033	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	3	13	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K6</u>
CA018-5034	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	5	15	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K6</u>
CA018-5035	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	8	18	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K6</u>
CA018-5036	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	10	20	2.3:1/1.6:1	2.0:1/1.5:1	320	<u>K6</u>
CA018-5037	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	13	23	2.3:1/1.6:1	2.0:1/1.5:1	340	<u>K6</u>
CA018-5038	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	15	25	2.3:1/1.6:1	2.0:1/1.5:1	360	<u>K6</u>
CA018-5039	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	18	28	2.3:1/1.6:1	2.0:1/1.5:1	400	<u>K6</u>
CA018-5220	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	20	30	2.3:1/1.6:1	2.0:1/1.5:1	420	<u>K6</u>
CA018-5223	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	23	33	2.3:1/1.6:1	2.0:1/1.5:1	450	<u>K6</u>
CA018-5224	0.5	18.0	50/55	±2.0/±1.5	3.2/2.7	24	34	2.3:1/1.6:1	2.0:1/1.5:1	500	<u>K6</u>
CA018-5042	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	0	10	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K6</u>
CA018-5043	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	3	13	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K6</u>
CA018-5044	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	5	15	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K6</u>
CA018-5045	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	8	18	2.3:1/1.6:1	2.0:1/1.5:1	300	<u>K6</u>
CA018-5046	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	10	20	2.3:1/1.6:1	2.0:1/1.5:1	320	<u>K6</u>
CA018-5047	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	13	23	2.3:1/1.6:1	2.0:1/1.5:1	340	<u>K6</u>
CA018-5048	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	15	25	2.3:1/1.6:1	2.0:1/1.5:1	360	<u>K6</u>
CA018-5049	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	18	28	2.3:1/1.6:1	2.0:1/1.5:1	400	<u>K6</u>
CA018-5320	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	20	30	2.3:1/1.6:1	2.0:1/1.5:1	420	<u>K6</u>
CA018-5323	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	23	33	2.3:1/1.6:1	2.0:1/1.5:1	450	<u>K6</u>
CA018-5324	0.5	18.0	50/55	±2.0/±1.5	3.0/2.5	24	34	2.3:1/1.6:1	2.0:1/1.5:1	500	<u>K6</u>

Ciao Wireless, Inc.

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / ciaowireless.com