



# 1.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 +/-15 VDC Current (mA) Nom/Max	Size
CA118-2001	1.0	18.0	18	±2.5	5.0	5	15	2.0:1/1.5:1	2.0:1/1.5:1	120	K2
CA118-2002	1.0	18.0	18	±2.5	5.0	8	18	2.0:1/1.5:1	2.0:1/1.5:1	130	K2
CA118-2003	1.0	18.0	18	±2.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	140	K2
CA118-2004	1.0	18.0	18	±2.5	5.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	150	K2
CA118-2005	1.0	18.0	17	±2.5	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	160	K2
CA118-2006	1.0	18.0	16	±2.5	5.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	200	K2
CA118-2020	1.0	18.0	14	±2.5	6.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K2
CA118-2022	1.0	18.0	14	±2.5	6.0	22	32	2.0:1/1.5:1	2.0:1/1.5:1	350	K2
CA118-2024	1.0	18.0	12	±2.5	6.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	400	K2
CA118-2026	1.0	18.0	18	±2.0	6.0	26	36	2.0:1/1.5:1	2.0:1/1.5:1	650	K2
CA118-2027	1.0	18.0	15/18	±2.0/±1.5	7.5/6.0	27/29	37	2.0:1/1.7:1	2.3:1/1.8:1	785	K3S
CA118-2028	1.0	18.0	16/19	±2.0/±1.5	7.5/6.0	28/30	38	2.0:1/1.7:1	2.3:1/1.8:1	800	K3S
CA118-2030	1.0	18.0	17/20	±2.0/±1.5	7.5/6.0	30/32	40	2.0:1/1.7:1	2.3:1/1.8:1	820	K3S
CA118-3001	1.0	18.0	26	±2.5	5.0	5	15	2.0:1/1.5:1	2.0:1/1.5:1	180	K3S
CA118-3002	1.0	18.0	26	±2.5	5.0	8	18	2.0:1/1.5:1	2.0:1/1.5:1	190	K3S
CA118-3003	1.0	18.0	26	±2.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3004	1.0	18.0	26	±2.5	5.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	210	K3S
CA118-3005	1.0	18.0	26	±2.5	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	220	K3S
CA118-3006	1.0	18.0	26	±2.5	5.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	260	K3S
CA118-3020	1.0	18.0	26	±2.5	5.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	345	K3S
CA118-3022	1.0	18.0	26	±2.5	6.0	22	32	2.0:1/1.5:1	2.0:1/1.5:1	425	K3S
CA118-3024	1.0	18.0	26	±2.5	6.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	750	K3S
CA118-3026	1.0	18.0	26	±2.5	6.0	26	36	2.0:1/1.5:1	2.0:1/1.5:1	800	K3S
CA118-3027	1.0	18.0	20/25	±2.0/±1.5	7.5/5.0	27	37	2.25:1/1.5:1	2.25:1/1.5:1	850*	K3S
CA118-3029	1.0	18.0	20/25	±2.0/±1.5	7.5/5.0	29/31	39	2.25:1/1.5:1	2.25:1/1.5:1	950*	K3S-NR
CA118-3030	1.0	18.0	25/28	±2.0/±1.5	6.0/4.0	30/32	40	2.0:1/1.7:1	2.3:1/1.8:1	900	K3S
CA118-3009	1.0	18.0	26	±2.5	4.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3010	1.0	18.0	26	±2.5	3.8	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)



# 1.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /+15 VDC Current (mA) Nom/Max	Size
CA118-4001	1.0	18.0	34	±2.5	5.0	5	15	2.0:1/1.5:1	2.0:1/1.5:1	240	K4
CA118-4002	1.0	18.0	34	±2.5	5.0	8	18	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4003	1.0	18.0	34	±2.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	260	K4
CA118-4004	1.0	18.0	34	±2.5	6.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	270	K4
CA118-4005	1.0	18.0	34	±2.5	6.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	280	K4
CA118-4006	1.0	18.0	34	±2.5	6.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	320	K4
CA118-4020	1.0	18.0	34	±2.5	6.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	405	K4
CA118-4022	1.0	18.0	34	±2.5	6.0	22	32	2.0:1/1.5:1	2.0:1/1.5:1	550	K4
CA118-4024	1.0	18.0	34	±2.5	6.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	750	K4
CA118-4026	1.0	18.0	34	±2.5	6.0	26	36	2.0:1/1.5:1	2.0:1/1.5:1	850	K4
CA118-4027	1.0	18.0	31/33	±2.0/±1.5	6.0/3.5	27/29	37	2.0:1/1.7:1	2.3:1/1.8:1	905	K4
CA118-4028	1.0	18.0	32/34	±2.0/±1.5	6.0/3.5	28/30	38	2.0:1/1.7:1	2.3:1/1.8:1	930	K4
CA118-4030	1.0	18.0	33/36	±2.0/±1.5	6.0/3.5	30/32	40	2.0:1/1.7:1	2.3:1/1.8:1	950	K4
CA118-4120	1.0	18.0	28/34	±2.5	6.0	20	32	2.0:1/1.5:1	2.0:1/1.5:1	550	K4
CA118-4120-1	1.0	18.0	28/35 <sup>1</sup>	±2.5	6.5/5.0	20	32	2.0:1/1.5:1	2.0:1/1.5:1	550	K3S
CA118-4120L-1	1.0	18.0	28/35 <sup>1</sup>	±2.5	8.0/5.0	20	32	2.0:1/1.5:1	2.0:1/1.5:1	550	K3S
CA118-4009	1.0	18.0	34	±2.5	4.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	260	K4
CA118-4010	1.0	18.0	34	±2.5	3.8	10	20	2.0:1/1.5:1	2.0:1/1.5:1	260	K4
CA118-4015	1.0	18.0	30/35	±2.0/±1.5	5.0/4.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	260	K4
CA118-4017	1.0	18.0	30/35	±2.0/±1.5	5.0/4.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	285	K4
CA118-3012	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	0	10	2.0:1/1.5:1	2.0:1/1.5:1	200	K4
CA118-3013	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	3	13	2.0:1/1.5:1	2.0:1/1.5:1	200	K4
CA118-3014	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	5	15	2.0:1/1.5:1	2.0:1/1.5:1	200	K4
CA118-3015	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	8	18	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3016	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	K3S
CA118-3017	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	13	23	2.0:1/1.5:1	2.0:1/1.5:1	240	K3S
CA118-3018	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	15	25	2.0:1/1.5:1	2.0:1/1.5:1	260	K3S
CA118-3019	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	18	28	2.0:1/1.5:1	2.0:1/1.5:1	300	K3S
CA118-3120	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	20	30	2.0:1/1.5:1	2.0:1/1.5:1	320	K3S
CA118-3123	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	23	33	2.0:1/1.5:1	2.0:1/1.5:1	350	K3S
CA118-3124	1.0	18.0	30/35	±2.0/±1.5	3.5/2.9	24	34	2.0:1/1.5:1	2.0:1/1.5:1	400	K3S

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)



# 1.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /+15 VDC Current (mA) Nom/Max	Size
CA118-3042	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	0	10	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3043	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	3	13	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3044	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	5	15	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3045	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	8	18	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3046	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	K3S
CA118-3047	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	13	23	2.0:1/1.5:1	2.0:1/1.5:1	240	K3S
CA118-3048	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	15	25	2.0:1/1.5:1	2.0:1/1.5:1	260	K3S
CA118-3049	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	18	28	2.0:1/1.5:1	2.0:1/1.5:1	300	K3S
CA118-3220	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	20	30	2.0:1/1.5:1	2.0:1/1.5:1	320	K3S
CA118-3223	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	23	33	2.0:1/1.5:1	2.0:1/1.5:1	350	K3S
CA118-3224	1.0	18.0	30/35	±2.0/±1.5	3.2/2.7	24	34	2.0:1/1.5:1	2.0:1/1.5:1	400	K3S
CA118-3000	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	0	10	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3031	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	3	13	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3032	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	5	15	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3033	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	8	18	2.0:1/1.5:1	2.0:1/1.5:1	200	K3S
CA118-3034	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	K3S
CA118-3035	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	13	23	2.0:1/1.5:1	2.3:1/1.5:1	220	K3S
CA118-3036	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	15	25	2.2:1/1.5:1	2.0:1/1.5:1	260	K3S
CA118-3037	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	18	28	2.0:1/1.5:1	2.0:1/1.5:1	300	K3S
CA118-3320	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	320	K3S
CA118-3323	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	350	K3S
CA118-3324	1.0	18.0	30/35	±2.0/±1.5	3.0/2.5	24	34	2.0:1/1.5:1	2.0:1/1.5:1	400	K3S
CA118-4012	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	0	10	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4013	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	3	13	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4014	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	5	15	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4015	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	8	18	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4016	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	10	20	2.0:1/1.5:1	2.0:1/1.5:1	270	K4
CA118-4017	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	13	23	2.0:1/1.5:1	2.0:1/1.5:1	290	K4
CA118-4018	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	15	25	2.0:1/1.5:1	2.0:1/1.5:1	280	K4
CA118-4019	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	18	28	2.0:1/1.5:1	2.0:1/1.5:1	350	K4
CA118-4220	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	20	30	2.0:1/1.5:1	2.0:1/1.5:1	370	K4
CA118-4223	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	23	33	2.0:1/1.5:1	2.0:1/1.5:1	400	K4
CA118-4224	1.0	18.0	40/45	±2.0/±1.5	3.5/2.9	24	34	2.0:1/1.5:1	2.0:1/1.5:1	450	K4

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)



## 1.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /+15 VDC Current (mA) Nom/Max	Size
CA118-4032	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	0	10	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4033	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	3	13	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4034	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	5	15	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4035	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	8	18	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4036	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	10	20	2.0:1/1.5:1	2.0:1/1.5:1	270	K4
CA118-4037	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	13	23	2.0:1/1.5:1	2.0:1/1.5:1	290	K4
CA118-4038	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	15	25	2.0:1/1.5:1	2.0:1/1.5:1	280	K4
CA118-4039	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	18	28	2.0:1/1.5:1	2.0:1/1.5:1	350	K4
CA118-4320	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	20	30	2.0:1/1.5:1	2.0:1/1.5:1	370	K4
CA118-4323	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	23	33	2.0:1/1.5:1	2.0:1/1.5:1	400	K4
CA118-4324	1.0	18.0	40/45	±2.0/±1.5	3.2/2.7	24	34	2.0:1/1.5:1	2.0:1/1.5:1	450	K4
CA118-4042	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	0	10	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4043	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	3	13	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4044	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	5	15	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4045	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	8	18	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-4046	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	270	K4
CA118-4047	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	13	23	2.0:1/1.5:1	2.0:1/1.5:1	290	K4
CA118-4048	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	15	25	2.2:1/1.5:1	2.0:1/1.5:1	280	K4
CA118-4049	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	18	28	2.0:1/1.5:1	2.0:1/1.5:1	350	K4
CA118-4420	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	370	K4
CA118-4423	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	400	K4
CA118-4424	1.0	18.0	40/45	±2.0/±1.5	3.0/2.5	24	34	2.0:1/1.5:1	2.0:1/1.5:1	450	K4
CA118-5012	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	0	10	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-5013	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	3	13	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-5014	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	5	15	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-5015	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	8	18	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA118-5016	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	10	20	2.0:1/1.5:1	2.0:1/1.5:1	270	K4
CA118-5017	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	13	23	2.0:1/1.5:1	2.0:1/1.5:1	290	K4
CA118-5018	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	15	25	2.0:1/1.5:1	2.0:1/1.5:1	280	K4
CA118-5019	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	18	28	2.0:1/1.5:1	2.0:1/1.5:1	350	K4
CA118-5120	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	20	30	2.0:1/1.5:1	2.0:1/1.5:1	370	K4
CA118-5123	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	23	33	2.0:1/1.5:1	2.0:1/1.5:1	400	K4
CA118-5124	1.0	18.0	50/55	±2.0/±1.5	3.5/2.9	24	34	2.0:1/1.5:1	2.0:1/1.5:1	450	K4

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)



## 1.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /+15 VDC Current (mA) Nom/Max	Size
CA118-5032	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	0	10	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA118-5033	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	3	13	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA118-5034	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	5	15	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA118-5035	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	8	18	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA118-5036	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	10	20	2.0:1/1.5:1	2.0:1/1.5:1	320	K4
CA118-5037	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	13	23	2.0:1/1.5:1	2.0:1/1.5:1	340	K4
CA118-5038	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	15	25	2.0:1/1.5:1	2.0:1/1.5:1	360	K4
CA118-5039	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	18	28	2.0:1/1.5:1	2.0:1/1.5:1	400	K4
CA118-5220	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	20	30	2.0:1/1.5:1	2.0:1/1.5:1	420	K4
CA118-5223	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	23	33	2.0:1/1.5:1	2.0:1/1.5:1	450	K4
CA118-5224	1.0	18.0	50/55	±2.0/±1.5	3.2/2.7	24	34	2.0:1/1.5:1	2.0:1/1.5:1	500	K4
CA118-5042	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	0	10	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA118-5043	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	3	13	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA118-5044	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	5	15	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA118-5045	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	8	18	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA118-5046	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	320	K4
CA118-5047	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	13	23	2.0:1/1.5:1	2.0:1/1.5:1	340	K4
CA118-5048	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	15	25	2.2:1/1.5:1	2.0:1/1.5:1	360	K4
CA118-5049	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	18	28	2.0:1/1.5:1	2.0:1/1.5:1	400	K4
CA118-5320	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	420	K4
CA118-5323	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	450	K4
CA118-5324	1.0	18.0	50/55	±2.0/±1.5	3.0/2.5	24	34	2.0:1/1.5:1	2.0:1/1.5:1	500	K4

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)