



## 6.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 +/-15 VDC Current (mA) Nom/Max	Size
CA618-2001	6.0	18.0	14	±1.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	100	K2
CA618-2002	6.0	18.0	14	±1.5	5.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	150	K2
CA618-2003	6.0	18.0	13	±1.5	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	200	K2
CA618-2004	6.0	18.0	12	±1.5	5.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	250	K2
CA618-2005	6.0	18.0	11	±1.5	6.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	300	K2
CA618-2006	6.0	18.0	10	±1.5	6.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	420	K2-SQCR
CA618-3001	6.0	18.0	20	±1.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	150	K3
CA618-3002	6.0	18.0	20	±1.5	5.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	200	K3
CA618-3003	6.0	18.0	19	±1.5	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	200	K3
CA618-3003B	6.0	18.0	21	±1.5	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	200	K3
CA618-3004	6.0	18.0	18	±1.5	5.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	200	K3
CA618-3005	6.0	18.0	17	±1.5	6.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	350	K3
CA618-3006	6.0	18.0	16	±2.0	6.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	550	K3
CA618-4001	6.0	18.0	26	±2.0	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	K4
CA618-4002	6.0	18.0	25	±2.0	5.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA618-4003	6.0	18.0	25	±2.0	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA618-4004	6.0	18.0	24	±2.0	5.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	350	K4
CA618-4005	6.0	18.0	23	±2.0	6.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	400	K4
CA618-4112	6.0	18.0	25	±2.5	5.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	700	K4
CA618-4006	6.0	18.0	22	±2.0	6.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	500	K4
CA618-256025	6.0	18.0	25	±2.0	6.0	25	35	2.0:1/1.5:1	2.0:1/1.5:1	700	K4
CA618-4008	6.0	18.0	20	±2.0	6.0	27	37	2.0:1/1.5:1	2.0:1/1.5:1	700	K4
CA618-256027	6.0	18.0	25	±2.0	6.0	27	37	2.0:1/1.5:1	2.0:1/1.5:1	700	K4
CA618-256030	6.0	18.0	25	±2.0	6.0	30	40	2.0:1/1.5:1	2.0:1/1.5:1	1600	K4
CA618-256033	6.0	18.0	25	±2.0	6.0	33	43	2.0:1/1.5:1	2.0:1/1.5:1	2000	K4
CA618-254010	6.0	18.0	25	±1.5	4.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	K4
CA618-254012	6.0	18.0	25	±1.5	4.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA618-254015	6.0	18.0	25	±1.5	4.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA618-254017	6.0	18.0	25	±1.5	4.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	350	K4
CA618-254020	6.0	18.0	25	±1.5	4.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K4
CA618-254023	6.0	18.0	25	±1.5	4.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	500	K4
CA618-254024	6.0	18.0	25	±1.5	4.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	550	K4
CA618-254025	6.0	18.0	25	±1.5	4.0	25	35	2.0:1/1.5:1	2.0:1/1.5:1	650	K3S
CA618-254027	6.0	18.0	25	±1.5	4.0	27	37	2.0:1/1.5:1	2.0:1/1.5:1	900	K4
CA618-254030	6.0	18.0	25	±1.5	4.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1600	K4-PA
CA618-254033	6.0	18.0	25	±1.5	4.0	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)



## 6.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /+15 VDC Current (mA) Nom/Max	Size
CA618-253510	6.0	18.0	25	±1.5	3.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	K4
CA618-253512	6.0	18.0	25	±1.5	3.5	12	23	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA618-253515	6.0	18.0	25	±1.5	3.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA618-253517	6.0	18.0	25	±1.5	3.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	350	K4
CA618-253520	6.0	18.0	25	±1.5	3.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K4
CA618-253523	6.0	18.0	25	±1.5	3.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	500	K4
CA618-253524	6.0	18.0	25	±1.5	3.5	24	34	2.0:1/1.5:1	2.0:1/1.5:1	550	K4
CA618-253525	6.0	18.0	25	±1.5	3.5	25	35	2.0:1/1.5:1	2.0:1/1.5:1	650	K4
CA618-253527	6.0	18.0	25	±1.5	3.5	27	37	2.0:1/1.5:1	2.0:1/1.5:1	900	K4
CA618-253530	6.0	18.0	25	±1.5	3.5	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1500	K4-PA
CA618-253533	6.0	18.0	25	±1.5	3.5	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA
CA618-253010	6.0	18.0	25	±1.5	3.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	K4
CA618-253012	6.0	18.0	25	±1.5	3.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA618-253015	6.0	18.0	25	±1.5	3.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA618-253017	6.0	18.0	25	±1.5	3.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	350	K4
CA618-253020	6.0	18.0	25	±1.5	3.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K4
CA618-253023	6.0	18.0	25	±1.5	3.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	500	K4
CA618-253024	6.0	18.0	25	±1.5	3.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	550	K4
CA618-253025	6.0	18.0	25	±1.5	3.0	25	35	2.0:1/1.5:1	2.0:1/1.5:1	650	K4
CA618-253027	6.0	18.0	25	±1.5	3.0	27	37	2.0:1/1.5:1	2.0:1/1.5:1	900	K4
CA618-253030	6.0	18.0	25	±1.5	3.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1500	K4-PA
CA618-253033	6.0	18.0	25	±1.5	3.0	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA
CA618-252510	6.0	18.0	25	±1.5	2.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	200	K4
CA618-252512	6.0	18.0	25	±1.5	2.5	12	23	2.0:1/1.5:1	2.0:1/1.5:1	250	K4
CA618-252515	6.0	18.0	25	±1.5	2.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	300	K4
CA618-252517	6.0	18.0	25	±1.5	2.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	350	K4
CA618-252520	6.0	18.0	25	±1.5	2.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K4
CA618-252523	6.0	18.0	25	±1.5	2.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	550	K4
CA618-252524	6.0	18.0	25	±1.5	2.5	24	34	2.0:1/1.5:1	2.0:1/1.5:1	550	K4
CA618-252525	6.0	18.0	25	±1.5	2.5	25	35	2.0:1/1.5:1	2.0:1/1.5:1	650	K4
CA618-252527	6.0	18.0	25	±1.5	2.5	27	37	2.0:1/1.5:1	2.0:1/1.5:1	900	K4
CA618-252530	6.0	18.0	25	±1.5	2.5	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1500	K4-PA
CA618-252533	6.0	18.0	25	±1.5	2.5	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)



## 6.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /+15 VDC Current (mA) Nom/Max	Size
CA618-5001	6.0	18.0	30	±2.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	250	K6
CA618-5002	6.0	18.0	30	±2.5	5.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-5003	6.0	18.0	30	±2.5	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-5004	6.0	18.0	30	±2.5	5.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-5005	6.0	18.0	30	±2.5	6.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-5006	6.0	18.0	30	±2.5	6.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	550	K6
CA618-306024	6.0	18.0	30	±2.5	6.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	700	K6
CA618-306025	6.0	18.0	30	±2.5	6.0	25	35	2.0:1/1.5:1	2.0:1/1.5:1	850	K6
CA618-306027	6.0	18.0	30	±2.5	6.0	27	37	2.0:1/1.5:1	2.0:1/1.5:1	900	K6
CA618-5101	6.0	18.0	30	±2.5	6.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1500	K4-PA
CA618-5102	6.0	18.0	30	±2.5	6.0	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA
CA618-304010	6.0	18.0	30	±2.0	4.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	250	K6
CA618-304012	6.0	18.0	30	±2.0	4.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-304015	6.0	18.0	30	±2.0	4.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-304017	6.0	18.0	30	±2.0	4.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-304020	6.0	18.0	30	±2.0	4.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-304023	6.0	18.0	30	±2.0	4.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	600	K6
CA618-304024	6.0	18.0	30	±2.0	4.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	650	K6
CA618-304025	6.0	18.0	30	±2.0	4.0	25	35	2.0:1/1.5:1	2.0:1/1.5:1	700	K6
CA618-304027	6.0	18.0	30	±2.0	4.0	27	37	2.0:1/1.5:1	2.0:1/1.5:1	900	K6
CA618-304030	6.0	18.0	30	±2.0	4.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1500	K4-PA
CA618-304033	6.0	18.0	30	±2.0	4.0	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA
CA618-303510	6.0	18.0	30	±2.0	3.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	250	K6
CA618-303512	6.0	18.0	30	±2.0	3.5	12	23	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-303515	6.0	18.0	30	±2.0	3.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-303517	6.0	18.0	30	±2.0	3.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-303520	6.0	18.0	30	±2.0	3.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-303523	6.0	18.0	30	±2.0	3.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	600	K6
CA618-303524	6.0	18.0	30	±2.0	3.5	24	34	2.0:1/1.5:1	2.0:1/1.5:1	650	K6
CA618-303525	6.0	18.0	30	±2.0	3.5	25	35	2.0:1/1.5:1	2.0:1/1.5:1	700	K6
CA618-303527	6.0	18.0	30	±2.0	3.5	27	37	2.0:1/1.5:1	2.0:1/1.5:1	900	K6
CA618-303530	6.0	18.0	30	±2.0	3.5	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1500	K4-PA
CA618-303533	6.0	18.0	30	±2.0	3.5	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)



## 6.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 +/-15 VDC Current (mA) Nom/Max	Size
CA618-303010	6.0	18.0	30	±2.0	3.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	250	K6
CA618-303012	6.0	18.0	30	±2.0	3.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-303015	6.0	18.0	30	±2.0	3.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-303017	6.0	18.0	30	±2.0	3.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-303020	6.0	18.0	30	±2.0	3.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-303023	6.0	18.0	30	±2.0	3.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	600	K6
CA618-303024	6.0	18.0	30	±2.0	3.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	650	K6
CA618-303025	6.0	18.0	30	±2.0	3.0	25	35	2.0:1/1.5:1	2.0:1/1.5:1	700	K6
CA618-302510	6.0	18.0	30	±2.0	2.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	250	K6
CA618-302512	6.0	18.0	30	±2.0	2.5	12	23	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-302515	6.0	18.0	30	±2.0	2.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-302517	6.0	18.0	30	±2.0	2.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-302520	6.0	18.0	30	±2.0	2.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-302523	6.0	18.0	30	±2.0	2.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	600	K6
CA618-302524	6.0	18.0	30	±2.0	2.5	24	34	2.0:1/1.5:1	2.0:1/1.5:1	650	K6
CA618-302525	6.0	18.0	30	±2.0	2.5	25	35	2.0:1/1.5:1	2.0:1/1.5:1	700	K6
CA618-6001	6.0	18.0	38	±2.5	5.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-6002	6.0	18.0	38	±2.5	5.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-6003	6.0	18.0	37	±2.5	5.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-6004	6.0	18.0	36	±2.5	5.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-6005	6.0	18.0	35	±2.5	6.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	500	K6
CA618-6006	6.0	18.0	34	±2.5	6.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	600	K6
CA618-356024	6.0	18.0	35	±2.5	6.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	650	K6
CA618-356025	6.0	18.0	35	±2.5	6.0	25	35	2.0:1/1.5:1	2.0:1/1.5:1	700	K6
CA618-6008	6.0	18.0	32	±2.5	6.0	27	37	2.0:1/1.5:1	2.0:1/1.5:1	800	K6
CA618-356027	6.0	18.0	35	±2.5	6.0	27	37	2.0:1/1.5:1	2.0:1/1.5:1	800	K6
CA618-6114	6.0	18.0	35	±2.5	6.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1200	K6+ISO
CA618-356030	6.0	18.0	35	±2.5	6.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1500	K6
CA618-6115	6.0	18.0	35	±2.5	6.0	32	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	BB+ISO
CA618-356033	6.0	18.0	35	±2.5	6.0	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)



## 6.0 GHz to 18.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 +/-15 VDC Current (mA) Nom/Max	Size
CA618-354010	6.0	18.0	35	±2.0	4.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-354012	6.0	18.0	35	±2.0	4.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-354015	6.0	18.0	35	±2.0	4.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-354017	6.0	18.0	35	±2.0	4.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-354020	6.0	18.0	35	±2.0	4.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	500	K6
CA618-354023	6.0	18.0	35	±2.0	4.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	660	K6
CA618-354024	6.0	18.0	35	±2.0	4.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	715	K6
CA618-354025	6.0	18.0	35	±2.0	4.0	25	35	2.0:1/1.5:1	2.0:1/1.5:1	800	K6
CA618-354027	6.0	18.0	35	±2.0	4.0	27	37	2.0:1/1.5:1	2.0:1/1.5:1	900	K6
CA618-354030	6.0	18.0	35	±2.0	4.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1500	K4-PA
CA618-354033	6.0	18.0	35	±2.0	4.0	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA
CA618-353510	6.0	18.0	35	±2.0	3.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-353512	6.0	18.0	35	±2.0	3.5	12	23	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-353515	6.0	18.0	35	±2.0	3.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-353517	6.0	18.0	35	±2.0	3.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-353520	6.0	18.0	35	±2.0	3.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	500	K6
CA618-353523	6.0	18.0	35	±2.0	3.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	660	K6
CA618-353524	6.0	18.0	35	±2.0	3.5	24	34	2.0:1/1.5:1	2.0:1/1.5:1	715	K6
CA618-353525	6.0	18.0	35	±2.0	3.5	25	35	2.0:1/1.5:1	2.0:1/1.5:1	800	K6
CA618-353527	6.0	18.0	35	±2.0	3.5	27	37	2.0:1/1.5:1	2.0:1/1.5:1	900	K6
CA618-353530	6.0	18.0	35	±2.0	3.5	30	38	2.0:1/1.5:1	2.0:1/1.5:1	1500	K4-PA
CA618-353533	6.0	18.0	35	±2.0	3.5	33	41	2.0:1/1.5:1	2.0:1/1.5:1	2000	K8-PA
CA618-353010	6.0	18.0	35	±2.0	3.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-353012	6.0	18.0	35	±2.0	3.0	12	23	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-353015	6.0	18.0	35	±2.0	3.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-353017	6.0	18.0	35	±2.0	3.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-353020	6.0	18.0	35	±2.0	3.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	500	K6
CA618-353023	6.0	18.0	35	±2.0	3.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	660	K6
CA618-353024	6.0	18.0	35	±2.0	3.0	24	34	2.0:1/1.5:1	2.0:1/1.5:1	715	K6
CA618-353025	6.0	18.0	35	±2.0	3.0	25	35	2.0:1/1.5:1	2.0:1/1.5:1	800	K6
CA618-352510	6.0	18.0	35	±2.0	2.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA618-352512	6.0	18.0	35	±2.0	2.5	12	23	2.0:1/1.5:1	2.0:1/1.5:1	350	K6
CA618-352515	6.0	18.0	35	±2.0	2.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	400	K6
CA618-352017	6.0	18.0	35	±2.0	2.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	450	K6
CA618-352520	6.0	18.0	35	±2.0	2.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	500	K6
CA618-352523	6.0	18.0	35	±2.0	2.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	660	K6
CA618-352524	6.0	18.0	35	±2.0	2.5	24	34	2.0:1/1.5:1	2.0:1/1.5:1	715	K6
CA618-352526	6.0	18.0	35	±2.0	2.5	25	35	2.0:1/1.5:1	2.0:1/1.5:1	800	K6

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)