



2.0 GHz to 10.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /+15 VDC Current (mA) Nom/Max	Size
CA210-2001	2.0	10.0	17	±2.0	4.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	120	K2
CA210-2002	2.0	10.0	17	±2.0	4.5	13	23	2.0:1/1.5:1	2.0:1/1.5:1	140	K2
CA210-2003	2.0	10.0	16	±2.0	4.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	150	K2
CA210-2004	2.0	10.0	16	±2.0	4.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	175	K2
CA210-2005	2.0	10.0	15	±2.5	5.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	225	K2
CA210-2006	2.0	10.0	15	±2.5	5.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	260	K2
CA210-3001	2.0	10.0	25	±2.0	4.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	180	K3
CA210-3002	2.0	10.0	25	±2.0	4.5	13	23	2.0:1/1.5:1	2.0:1/1.5:1	200	K3
CA210-3003	2.0	10.0	24	±2.0	4.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	210	K3
CA210-3004	2.0	10.0	24	±2.0	4.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	235	K3
CA210-3005	2.0	10.0	23	±2.5	5.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	285	K3
CA210-3006	2.0	10.0	23	±2.5	5.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	320	K3
CA210-4001	2.0	10.0	33	±2.0	4.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	240	K4
CA210-4002	2.0	10.0	33	±2.0	4.5	13	23	2.0:1/1.5:1	2.0:1/1.5:1	260	K4
CA210-4003	2.0	10.0	32	±2.0	4.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	270	K4
CA210-4004	2.0	10.0	32	±2.0	4.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	305	K4
CA210-4005	2.0	10.0	31	±2.5	5.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	355	K4
CA210-4006	2.0	10.0	31	±2.5	5.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	380	K4
CA210-5001	2.0	10.0	39	±2.0	4.5	10	20	2.0:1/1.5:1	2.0:1/1.5:1	300	K6
CA210-5002	2.0	10.0	39	±2.0	4.5	13	23	2.0:1/1.5:1	2.0:1/1.5:1	320	K6
CA210-5003	2.0	10.0	38	±2.0	4.5	15	25	2.0:1/1.5:1	2.0:1/1.5:1	330	K6
CA210-5004	2.0	10.0	38	±2.0	4.5	17	27	2.0:1/1.5:1	2.0:1/1.5:1	365	K6
CA210-5005	2.0	10.0	37	±2.5	5.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	415	K6
CA210-5006	2.0	10.0	37	±2.5	5.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	440	K6

Ciao Wireless, Inc.

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / ciaowireless.com