



5.85 GHz to 6.425 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /+15 VDC Current (mA) Nom/Max	Size
CA56-2016	5.85	6.425	24	±0.5	2.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	100	C2
CA56-2017	5.85	6.425	24	±0.5	1.6	10	20	2.0:1/1.5:1	2.0:1/1.5:1	100	C2
CA56-2018	5.85	6.425	24	±0.5	1.4	10	20	2.0:1/1.5:1	2.0:1/1.5:1	100	C2
CA56-2019	5.85	6.425	24	±0.5	1.2	10	20	2.0:1/1.5:1	2.0:1/1.5:1	100	C2
CA56-2020	5.85	6.425	24	±0.5	1.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	100	C2
CA56-2023	5.85	6.425	20	±0.5	2.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	130	C2
CA56-2024	5.85	6.425	20	±0.5	2.2	20	30	2.0:1/1.5:1	2.0:1/1.5:1	180	C2
CA56-2025	5.85	6.425	20	±0.5	2.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	230	C2
CA56-2026	5.85	6.425	20	±0.5	2.7	27	35	2.0:1/1.5:1	2.0:1/1.5:1	450	C2
CA56-2027	5.85	6.425	20	±0.5	3.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	600	C2
CA56-3016	5.85	6.425	30	±0.5	2.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	120	C3
CA56-3017	5.85	6.425	30	±0.5	1.6	10	20	2.0:1/1.5:1	2.0:1/1.5:1	120	C3
CA56-3018	5.85	6.425	30	±0.5	1.4	10	20	2.0:1/1.5:1	2.0:1/1.5:1	120	C3
CA56-3019	5.85	6.425	30	±0.5	1.2	10	20	2.0:1/1.5:1	2.0:1/1.5:1	120	C3
CA56-3020	5.85	6.425	30	±0.5	1.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	120	C3
CA56-3023	5.85	6.425	30	±0.5	2.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	180	C3
CA56-3024	5.85	6.425	30	±0.5	2.2	20	30	2.0:1/1.5:1	2.0:1/1.5:1	230	C3
CA56-3025	5.85	6.425	30	±0.5	2.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	280	C3
CA56-3026	5.85	6.425	30	±0.5	2.7	27	35	2.0:1/1.5:1	2.0:1/1.5:1	500	C3
CA56-3027	5.85	6.425	30	±0.5	3.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	850	C3
CA56-4016	5.85	6.425	42	±0.5	2.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	180	C4
CA56-4017	5.85	6.425	42	±0.5	1.6	10	20	2.0:1/1.5:1	2.0:1/1.5:1	180	C4
CA56-4018	5.85	6.425	42	±0.5	1.4	10	20	2.0:1/1.5:1	2.0:1/1.5:1	180	C4
CA56-4019	5.85	6.425	42	±0.5	1.2	10	20	2.0:1/1.5:1	2.0:1/1.5:1	180	C4
CA56-4020	5.85	6.425	42	±0.5	1.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	180	C4
CA56-4023	5.85	6.425	40	±0.5	2.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	230	C4
CA56-4024	5.85	6.425	40	±0.5	2.2	20	30	2.0:1/1.5:1	2.0:1/1.5:1	280	C4
CA56-4025	5.85	6.425	40	±0.5	2.5	23	33	2.0:1/1.5:1	2.0:1/1.5:1	330	C4
CA56-4026	5.85	6.425	40	±0.5	2.7	27	35	2.0:1/1.5:1	2.0:1/1.5:1	600	C4
CA56-4027	5.85	6.425	40	±0.5	3.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	750	C4
CA56-5016	5.85	6.425	56	±0.5	2.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	C6
CA56-5017	5.85	6.425	56	±0.5	1.6	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	C6
CA56-5018	5.85	6.425	56	±0.5	1.4	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	C6
CA56-5019	5.85	6.425	56	±0.5	1.2	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	C6
CA56-5020	5.85	6.425	56	±0.5	1.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	C6

Ciao Wireless, Inc.

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / ciaowireless.com