



## 2.0 GHz to 6.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12/+15 VDC Current (mA) Nom/Max	Size
CA26-1001	2.0	6.0	13	±1.0	4.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	60	XK2
CA26-1002	2.0	6.0	13	±1.0	4.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	70	XK2
CA26-1003	2.0	6.0	13	±1.0	4.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	100	XK2
CA26-1004	2.0	6.0	12	±1.0	4.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	130	XK2
CA26-1005	2.0	6.0	11	±1.0	4.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	145	XK2
CA26-1006	2.0	6.0	10	±1.0	4.0	22	32	2.0:1/1.5:1	2.0:1/1.5:1	185	XK2
CA26-1021	2.0	6.0	13	±1.0	3.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	60	XK2
CA26-1022	2.0	6.0	13	±1.0	3.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	70	XK2
CA26-1023	2.0	6.0	13	±1.0	3.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	100	XK2
CA26-1024	2.0	6.0	12	±1.0	3.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	130	XK2
CA26-1025	2.0	6.0	11	±1.0	3.0	20	30	2.0:1/1.5:1	2.0:1/1.5:1	145	XK2
CA26-1026	2.0	6.0	10	±1.0	3.0	22	32	2.0:1/1.5:1	2.0:1/1.5:1	185	XK2
CA26-2001	2.0	6.0	20	±1.0	3.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	90	XK2
CA26-2002	2.0	6.0	20	±1.0	3.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	100	XK2
CA26-2003	2.0	6.0	20	±1.0	3.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	130	XK2
CA26-2004	2.0	6.0	19	±1.0	3.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	160	XK2
CA26-2005	2.0	6.0	19	±1.0	3.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	185	XK2
CA26-2006	2.0	6.0	18	±1.0	4.0	23	32	2.0:1/1.5:1	2.0:1/1.5:1	220	XK2
CA26-2007	2.0	6.0	16	±1.0	4.5	25	33	2.0:1/1.5:1	2.0:1/1.5:1	350	XK2
CA26-2008	2.0	6.0	15	±1.5	5.0	27	35	2.0:1/1.5:1	2.0:1/1.5:1	450	XK2
CA26-2009	2.0	6.0	15	±1.5	5.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	600	XK2
CA26-2021	2.0	6.0	20	±1.0	2.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	90	XK2
CA26-2022	2.0	6.0	20	±1.0	2.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	100	XK2
CA26-2023	2.0	6.0	20	±1.0	2.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	130	XK2
CA26-3001	2.0	6.0	28	±1.0	3.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	150	XK2
CA26-3002	2.0	6.0	28	±1.0	3.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	160	XK2
CA26-3003	2.0	6.0	28	±1.0	3.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	200	XK2
CA26-3004	2.0	6.0	27	±1.0	3.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	220	XK2
CA26-3005	2.0	6.0	27	±1.0	3.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	240	XK2
CA26-3006	2.0	6.0	26	±1.0	4.0	23	32	2.0:1/1.5:1	2.0:1/1.5:1	280	XK2
CA26-3007	2.0	6.0	24	±1.0	4.5	25	33	2.0:1/1.5:1	2.0:1/1.5:1	400	XK2
CA26-3008	2.0	6.0	23	±1.5	5.0	27	35	2.0:1/1.5:1	2.0:1/1.5:1	600	C3
CA26-3009	2.0	6.0	23	±2.0	5.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	800	C4
CA26-3021	2.0	6.0	28	±1.0	2.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	150	XK2
CA26-3022	2.0	6.0	28	±1.0	2.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	160	XK2
CA26-3023	2.0	6.0	28	±1.0	2.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	200	XK2
CA26-4001	2.0	6.0	35	±1.0	3.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	XK2
CA26-4002	2.0	6.0	35	±1.0	3.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	230	XK2
CA26-4003	2.0	6.0	35	±1.0	3.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	270	XK2
CA26-4004	2.0	6.0	34	±1.0	3.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	290	XK2
CA26-4005	2.0	6.0	34	±1.0	3.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	310	XK2
CA26-4006	2.0	6.0	33	±1.0	4.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	350	XK2
CA26-4007	2.0	6.0	31	±1.0	4.5	25	33	2.0:1/1.5:1	2.0:1/1.5:1	470	XK2
CA26-4008	2.0	6.0	30	±1.5	5.0	27	35	2.0:1/1.5:1	2.0:1/1.5:1	620	XK2
CA26-4009	2.0	6.0	30	±2.5	5.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	770	XK2
CA26-4021	2.0	6.0	35	±1.0	2.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	220	XK2
CA26-4022	2.0	6.0	35	±1.0	2.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	230	XK2
CA26-4023	2.0	6.0	35	±1.0	2.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	270	XK2

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)



## 2.0 GHz to 6.0 GHz

Model No.	Frequency 1 GHz	Frequency 2 GHz	Gain dB (Min/Typ)	Flatness dB (Max/Typ)	Noise dB (Max/Typ)	P-1dB dBm (Min/Typ)	IP3 dBm (Typ)	VSWR Input (Max/Typ)	VSWR Output (Max/Typ)	+12 /+15 VDC Current (mA) Nom/Max	Size
CA26-5001	2.0	6.0	42	±1.5	3.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	300	XK3
CA26-5002	2.0	6.0	42	±1.5	3.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	310	XK3
CA26-5003	2.0	6.0	42	±1.5	3.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	350	XK3
CA26-5004	2.0	6.0	41	±1.5	3.0	17	27	2.0:1/1.5:1	2.0:1/1.5:1	370	XK3
CA26-5005	2.0	6.0	41	±1.5	3.5	20	30	2.0:1/1.5:1	2.0:1/1.5:1	390	XK3
CA26-5006	2.0	6.0	40	±1.5	4.0	23	33	2.0:1/1.5:1	2.0:1/1.5:1	430	XK3
CA26-5007	2.0	6.0	38	±1.0	4.5	25	33	2.0:1/1.5:1	2.0:1/1.5:1	550	XK3
CA26-5008	2.0	6.0	37	±1.5	5.0	27	35	2.0:1/1.5:1	2.0:1/1.5:1	700	XK3
CA26-5009	2.0	6.0	37	±2.5	5.0	30	38	2.0:1/1.5:1	2.0:1/1.5:1	850	XK3
CA26-5021	2.0	6.0	42	±1.5	2.0	10	20	2.0:1/1.5:1	2.0:1/1.5:1	300	XK3
CA26-5022	2.0	6.0	42	±1.5	2.0	13	23	2.0:1/1.5:1	2.0:1/1.5:1	310	XK3
CA26-5023	2.0	6.0	42	±1.5	2.0	15	25	2.0:1/1.5:1	2.0:1/1.5:1	350	XK3
CA26-7020	2.0	6.0	70/75	±2.0/±1.0	2.5/1.6	20/22	30	2.0:1/1.5:1	2.0:1/1.5:1	550	DUAL XK2
CA26-7020U	2.0	6.0	70/75	±2.0/±1.0	2.5/1.6	20/22	30	2.0:1/1.5:1	2.0:1/1.5:1	550	DUAL-XK2-U

**Ciao Wireless, Inc.**

4000 Via Pescador / Camarillo / CA 93012

Tel (805) 389-3224 / Fax (805) 389-3629 / [ciaowireless.com](http://ciaowireless.com)